LEOCH
理士电池®
LEOCH BATTERY

DJW12-9.0



Applications

- Network connection equipment of communication system
- Power system of special network or local area network
- UPS, standby power supply Power station systems
- Railway and marine systems



Specification

Nominal Voltage		12V
Nominal Capacity(20HR)		9.0Ah
Dimension	Length Width Container Height Total Height (with Terminal)	151mm (5.95 in.) 65mm (2.56 in.) 93.5mm (3.68 in.) 99mm (3.90 in.)
Approx Weight		2.50 Kg (5.5 lbs)
Terminal		250(T2)
Container Material		ABS
Rated Capacity (25°C)	C20(0.450A,1.60V/cell) C10(0.84A,1.60V/cell) C5(1.56A,1.60V/cell) C3(2.42A,1.60V/cell) C1(6.20A,1.60V/cell)	9.00 Ah 8.40 Ah 7.80 Ah 7.26 Ah 6.20 Ah
Max. Discharge Current		127.5A (5s)
Internal Resistance		⩽ 24.0mΩ
Operating Temp.Range	Discharge Charge Storage	-20°C~50°C (-4°F~122°F) -5°C~45°C (23°F~113°F) -20°C~45°C (-4°F~113°F)
Nominal Operating Temp. Range		25°C±3°C (77°F±5°F)
Standby Use (25°C)	Charging Current Charging Voltage Temp. Coefficient	≤2.70 A 13.5V~13.8V -3mV/cell/°C
Capacity affected by Temperature	40°C (104°F) 25°C (77°F) 0°C (32°F)	106% 100% 86%
Self Discharge		≤2% per month at 20°C

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	60min	90min	120min	180min	240min	300min	360min	480min	600min	1200min
1.85V/cell	30.0	21.0	16.7	12.7	9.70	7.00	5.70	4.11	3.17	2.25	1.75	1.46	1.24	0.97	0.78	0.400
1.80V/cell	33.0	23.5	17.4	13.2	10.00	7.10	5.80	4.18	3.22	2.29	1.78	1.48	1.26	0.98	0.79	0.425
1.75V/cell	36.0	24.0	18.2	13.8	10.20	7.30	5.90	4.25	3.27	2.32	1.80	1.50	1.27	0.99	0.80	0.430
1.70V/cell	39.0	25.0	18.9	14.3	10.50	7.40	6.00	4.32	3.32	2.36	1.83	1.52	1.29	1.00	0.81	0.440
1.67V/cell	42.0	25.5	19.3	14.9	10.60	7.50	6.10	4.36	3.35	2.38	1.84	1.53	1.30	1.01	0.82	0.445
1.60V/cell	45.0	26.5	19.5	15.4	10.90	7.70	6.20	4.46	3.42	2.42	1.89	1.56	1.33	1.04	0.84	0.450

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	60min	90min	120min	180min	240min	300min	360min	480min	600min	1200min
1.85V/cell	58.6	41.5	32.2	25.3	19.0	13.6	11.20	8.03	6.20	4.43	3.45	2.88	2.45	1.92	1.55	0.84
1.80V/cell	62.0	43.8	33.9	26.0	19.3	13.8	11.40	8.14	6.28	4.49	3.50	2.91	2.48	1.94	1.57	0.85
1.75V/cell	64.0	45.3	35.0	27.2	19.7	14.0	11.5	8.25	6.37	4.54	3.54	2.95	2.51	1.96	1.59	0.86
1.70V/cell	68.0	47.2	36.0	28.3	20.0	14.2	11.7	8.36	6.45	4.60	3.58	2.98	2.54	1.99	1.61	0.87
1.67V/cell	70.6	48.7	36.5	29.5	20.2	14.4	11.8	8.43	6.50	4.63	3.60	3.00	2.56	2.00	1.62	0.87
1.60V/cell	73.6	50.3	37.0	30.6	20.7	14.7	12.0	8.57	6.61	4.71	3.66	3.05	2.59	2.03	1.64	0.90

Specifications subject to change without notice.

ISO9001 ISO14001 MH26866 Intertek ETL SEMKO CE EMC tested

Constant current discharge curve



Constant power discharge curve



Curve of Battery Floating Charge



Curve of Floating & Cycle Service Life



Cycle Life in Relation to Depth of Discharge



Self discharging curves



Sales Office

China sales office:
Add:5th Floor,Xinbaohui Bldg.,Nanhai Blvd., Nanshan,Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail:export@leoch.com
Http://www.leoch.com

HongKong sales office:
Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road, Tsuen Wan, New Territories, Hong Kong
Tel: +852 35786666
Fax: +852 21170016
E-mail: sales.hk@leoch.com

Singapore sales office:
Add: No. 1 Tech Park Crescent, Singapore 638131
Tel: +65 68636078
Fax: +65 68636079
Email sales.sg@Leoch.com
Http://www.leoch.com

North America sales office:
Add: 19751 Descartes, Unit A, Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.com

Europe sales office:
Add: 9B Wheatstone Court. Waterwells Business Park, Gloucester, GL2-2AQ, UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 (0)1452-690125
E-mail: Sales.Europe@leoch.com

Publication No.: LB-DJW12-9.0-PD-201351-V1.0-202111